



# X11S6S

## One-Phase, 60Hz@1800RPM



### Genset Specification

Genset Model	Prime Power		Standby Power		Structure Type		Amps(A)			dBA @7m	Engine Model	Alternator Model	Dimension L x W x H (mm)	Weight (kg)	Tank (L)
	kVA	kW	kVA	kW			220V	230V	240V						
X11S6S	11.3	9	13	10	Soundproof	RS	51.1	48.8	46.9	N/A	D1105-BG	PI044H	1932 x 898 x 1310	652	100

### Engine Specification

Engine Model	Output Power (kw)	Cyl.	Gov.	Asp.	Displacement(L)	100%Cons (L/h)	Total Lubrication Capacity (L)	Total Coolant Capacity (L)
D1105-BG	11.5	3L	M	NA	1.1	2	5.1	6.4

### Configuration

	Genset Model	X11S6S
Engine	4-Stroke Water-cooled Diesel Engine	●
	Industrial Silencer	●
	Switch in the Negative Pole	●
	Oil Sump Pump	●
	Water Jacket Preheater220/240V	○
	Oil Preheater	○
Alternator	Standard Air Filter	●
	PMG	○
	Anti-condensing Heater	○
	Winding Temperature Measuring Instrument	○
	Single Bearing,Class Hinsulation,IP23	●
	Alternator Preheater	○
Cooling Systems	AVR	●
	Radiator for 45°C	●
	Coolant Integrated with Genset	●
	Coolant Protection Port	●
Starting Systems	Shelter of Water Tank	●
	Start-up and Charging	●
	Batteries with Cables and Switch	●
Control Systems	Protecting Jacket of Solenoid Terminal	●
	Battery Charger	●
	Key Start	●
	AMF	○
	Paralleling	×

	Genset Model	X11S6S
Fuel Systems	Breather Valve	●
	Fuel Level Sensor	●
	Fuel T-valves	○
Canopy and Soundproof Configuration	Outside Refueling	×
	Outside Watering	×
	Rain Hat of Hush Pipe	×
	Lifting Lugs	×
	Shock Absorbers	●
	Emergency Stop Button Outlaid	●
	Controls Cabinet with Windows and Doors	×
Bases	Air Inlet	×
	Air Outlet	×
	Silencer	●
	Base Fuel Tank	●
	Holes for Forklift	×
	Pulling Slots	●
Materials with Gensets	Wiring Hole	●
	Earthed Protection	●
	Drain Outlet	●
	Parts Manual	●
	Operation Manual	●
	Warranty Manual	●
	Records Notebook of Maintenance	●

Standard: ● Optional: ○ Impossible: ×

### Color & Size (mm)



Also available in the following voltages: 220V , 230V , 240V; (2) The weights are approximate and without fuel; \*Ambient reference conditions: 1,000 mbar, 27°C, 30% relative humidity. Rating according to ISO 3046 and 8528.